

Working radius (m)	Boom length (m)													
	10.0	13.0	16.0	19.0	22.0	25.0	28.0	31.0	34.0	37.0	40.0	43.0	46.0	49.0
3.0	40.0													
3.7	40.0	40.0												
4.0	34.60	34.50	33.15/4.1											
4.5	28.95	28.85	28.75	27.60/4.6										
5.0	24.35	24.25	24.15	24.05	22.80/5.2	19.05/5.8								
6.0	18.50	18.40	18.35	18.30	18.20	18.15	16.65/6.4							
7.0	14.90	14.80	14.75	14.65	14.60	14.50	14.45	14.40	13.10/7.5					
8.0	12.40	12.30	12.25	12.15	12.10	12.00	11.95	11.90	11.85	11.75	10.60/8.5			
9.0	10.60	10.55	10.45	10.40	10.30	10.25	10.15	10.10	10.00	9.95	9.90	9.80	8.80/9.5	
10.0	9.60/9.7	9.15	9.10	9.00	8.95	8.85	8.80	8.75	8.65	8.60	8.55	8.45	8.15	8.00
12.0		7.20	7.15	7.05	6.95	6.90	6.85	6.80	6.75	6.65	6.60	6.55	6.45	6.30
14.0		6.95/12.3	5.85	5.75	5.65	5.60	5.55	5.50	5.40	5.35	5.30	5.20	5.10	4.95
16.0			5.40/14.9	4.85	4.75	4.65	4.60	4.50	4.45	4.40	4.30	4.20	4.15	4.05
18.0				4.35/17.5	4.10	4.00	3.95	3.85	3.75	3.65	3.60	3.50	3.45	3.35
20.0					3.55	3.45	3.35	3.30	3.20	3.15	3.10	3.00	2.95	2.85
22.0						3.00	2.90	2.80	2.75	2.65	2.55	2.50	2.45	2.35
24.0						2.80/22.7	2.50	2.40	2.35	2.25	2.15	2.10	2.05	1.95
26.0							2.30/25.3	2.10	2.00	1.90	1.85	1.80	1.75	1.65
28.0								1.90	1.80	1.70	1.55	1.50	1.45	1.35
30.0									1.55	1.40	1.30	1.20	1.15	1.05
32.0									1.50/30.5	1.20	1.10	1.00	0.95	0.85